20 Clay Brick Way
Lantz, NS B2S 3G4
(902) 883-2201
salesinfo@shawbrick.ca
shawbrick.ca

Olde English

20 Clay Brick Way
Lantz, NS B2S 3G4
(902) 883-2201
salesinfo@shawbrick.ca
shawbrick.ca

Clay brick with century-old warmth and character.
The Olde English Collection from Shaw Brick combines the timeless charm of century-old brickwork with the exceptional strength and durability of modern craftsmanship. Each brick is uniquely textured and shaded, featuring subtle colour variations and a distressed surface that adds authentic character to any project. This collection is perfect for creating distinctive, enduring designs with a touch of historical elegance.

COLOUR

Essex

Winchester

SHAPE


Max 57


Metric Modular

TEXTURE

Rustic

ADDITIONAL INFORMATION/SPECIFICATIONS

BRICK MEASUREMENT CHART

Sizes	Metric	Imperial	Approximate Weight	Pieces per Pallet	Coverage
Modular	57 x 90 x 190 mm	2 1/4" x 3 1/2" x 7 5/8"	4 lbs	500	7 pieces/sq. ft.
Max 57	57 x 90 x 255 mm	2 1/4" x 3 1/2" x 10 1/8"	5 lbs	400	5.2 pieces/sq. ft.

20 Clay Brick Way
Lantz, NS B2S 3G4
(902) 883-2201
salesinfo@shawbrick.ca
shawbrick.ca

Minimum Compressive Strength – Gross Area MPa (P.S.I.)
Red: 80-100 (11,000-14,000)
Brown: 70-90 (10,000-13,000)
Buff: 65-85 (9,500-12,000)

Maximum Water Absorption (24 hr. %)
Red: 1 – 3
Brown: 2 – 4
Buff: 6 – 8

Maximum Saturation Coefficient
Red: 0.65 – 0.78
Brown: 0.50 – 0.70
Buff: 0.70 – 0.78

Maximum Initial Rate of Absorption
Red: 1g/min/5,000mm2
Brow: 5g/min/20,000mm2
Buff: 10g/min/20,000mm2

Freeze Thaw % After 50 Cycles – Meets Requirements