

## **TAPESTRY GREY 1.5%**



### **A rather refined Clay Brick with a delicate texture**

The Tapestry Collection of Clay Bricks from Shaw Brick features a delicate, lightly-textured finish that lends a refined character of unequalled depth and warmth.

While its understated speckled texture is reminiscent of age-old tapestries found in museums, this brick has all of the modern characteristics that Shaw Brick is known for - long-lasting performance, positive thermal and acoustical properties, eco-friendliness while adding incredible value to your home.

### **New colour ranges added this year**

Our designers are always keeping abreast of the latest architectural brick design trends and we are proud to introduce three new colour ranges this year: a contemporary Platinum Range, a full-bodied Merlot Range and an exquisite Pure Black Brick - all of which are top trending brick colours now.

The Tapestry Brick Collection is also available in Red Range, Brown Range, Magnum Brown Range, Charcoal Range, Mingled Shades, Flashed Range, Manganese Dark Range, Buff Range, and Grey Range.

Drop into a [Shaw Retail Centre](#) or one of our [independent dealers](#) to see samples of these bricks for sale and to learn more about any product in the Shaw Masonry Collection.



20 Clay Brick Way

Lantz, NS B2S 3G4

(902) 883-2201

salesinfo@shawbrick.ca

shawbrick.ca

## SPECIFICATIONS

### Brick Measurement Chart

Sizes	Metric	Imperial	Approximate Weight	Pc/Pallet	Coverage
Modular	57x90x190mm	2 ¼" x 3 1/2" x 7 5/8"	4lbs	500	7 pcs/sqft
Saxon	90x90x190mm	3 ½" x 3 ½" x 7 5/8"	6lbs	305	4.9 pcs/sqft
Max 57	57x90x255mm	2 ¼" x 3 ½" x 10 1/8"	5lbs	400	5.2 pcs/sqft
Ontario	60x102x213mm	2 3/8" x 4" x 8 3/8"	5lbs	395	6 pcs/sqft
CSR	70x90x230	2 3/4" x 3 1/2" x 9 1/16"	6lbs	380	4.9 pcs/sqft
MAX	79x90x290	3 1/8" x 3 1/2" x 10 1/8"	7lbs	276	3.9 pcs/sqft
Slender	12.7x90x190mm	1/2" x 3 1/2" x 7 5/8"	28lbs/box	34pcs/box	7 pcs/ sqft

**Note:** Not all bricks are available in all sizes as indicated. Please contact your Shaw Brick Sales Representative or email salesinfo@shawbrick.ca for minimum special order quantities and production lead times.

### Clay Brick Product Specifications

CSA STANDARD VS. SHAW – TYPICAL TEST REPORT				
Property	CSA Standard A82-06	SHAW BRICK		
		Red	Brown	Buff
Minimum Compressive Strength Gross Area MPa (P.S.I.)	20.68 (3,000)	80 – 100 (11,000 – 14,000)	70 – 90 (10,000 – 13,000)	65-85 (9,500 – 12,000)
Maximum Water Absorption 24 hr. %	8.0	1 – 3	2 – 4	6 – 8
Maximum Saturation Coefficient	0.78	0.65 – 0.78	0.50 – 0.70	0.70 – 0.78
Maximum Initial Rate of Absorption	30g/min/ 20,000mm <sup>2</sup>	1 – 5	5 – 20	10 – 20
Freeze Thaw % After 50 Cycles	Less than 0.5% loss in dry mass	Meets Requirements		

To view more photos and for more information on this product, visit: [shawbrick.ca/products/tapestry-grey-1-5/](http://shawbrick.ca/products/tapestry-grey-1-5/)